


GOGREEN

ENGINEERED TURF PRODUCTS



SCAN FOR WEBSITE



PETMAXX™ 50

KEY FEATURES

- Our Superior PETMAXX® Tuft binding technology provides a near dig proof backing
- AQUAMAXX® Fast drainage technology prevents lingering pet odors and bacteria buildup.
- Highest Quality Primary Backing - Thermally stable and wrinkle free
- Enhanced fiber memory creates increased resilience while giving a soft feel and realistic look
- No toxic chemicals or lead used in any products.



PET MAXX

RECOMMENDED APPLICATIONS



FOOT TRAFFIC



PRODUCT SPECIFICATIONS

| | |
|---------------|-------------------------------------------|
| YARN TYPE: | POLYETHYLENE MONOFILAMENT & POLYPROPYLENE |
| YARN COLOR: | SPORT GREEN, APPLE GREEN, & OLIVE GREEN |
| THATCH COLOR: | FIELD GREEN & TAN |
| FACE WEIGHT: | 50 OZ/SY |
| PILE HEIGHT: | 1" |
| BACKING: | 16 OZ BLACK URETHANE |
| WARRANTY: | 15 YEAR PRO RATED WARRANTY |

844.368.4765 | WWW.GOGREENSYNTURF.COM





GOGREEN

ENGINEERED TURF PRODUCTS

PETMAXX™ 50

| | |
|--------------------------------------------------|------------|
| AATCC 134 - ANTI-STATIC | N/A |
| ASTM C1028 - STATIC/FRICTION | N/A |
| ASTM D1335 - TUFT BIND | 12 LB |
| ASTM F2765 - LEAD LEVELS | <0.01 PPM |
| ASTM D2859 - FLAMMABILITY (PILL TEST) | PASS |
| ASTM E648 - FLAMMABILITY (CRITICAL RADIANT FLUX) | CLASS I |
| ASTM 5034 - GRAB TEAR STRENGTH | N/A |
| ASTM F1951 - ADA WHEELCHAIR | N/A |
| ASTM F1551 - WATER PERMEABILITY | >600 IN/HR |
| ASTM E108 - FIRE TEST (ROOF DECKS) | N/A |
| ASTM E84 - SURFACE FLAMMABILITY/SMOKE DENSITY | N/A |
| ASTM 1292 - IMPACT ATTENUATION | PASS |



PET MAXX