


GOGREEN

ENGINEERED TURF PRODUCTS



SCAN FOR WEBSITE



PETMAXX™ 75

KEY FEATURES

- Our Superior PETMAXX® Tuft binding technology provides a near dig proof backing
- AQUAMAXX® Fast drainage technology prevents lingering pet odors and bacteria buildup.
- Highest Quality Primary Backing - Thermally stable and wrinkle free
- Enhanced fiber memory creates increased resilience while giving a soft feel and realistic look
- No toxic chemicals or lead used in any products.



PET MAXX

RECOMMENDED APPLICATIONS



FOOT TRAFFIC



PRODUCT SPECIFICATIONS

YARN TYPE:	POLYETHYLENE MONOFILAMENT & POLYPROPYLENE
YARN COLOR:	SPORT GREEN, APPLE GREEN, & OLIVE GREEN
THATCH COLOR:	FIELD GREEN & TAN
FACE WEIGHT:	75 OZ/SY
PILE HEIGHT:	1 7/8"
BACKING:	16 OZ BLACK URETHANE
WARRANTY:	15 YEAR PRO RATED WARRANTY

844.368.4765 | WWW.GOGREENSYNTURF.COM





GOGREEN

ENGINEERED TURF PRODUCTS

PETMAXX™ 75

AATCC 134 - ANTI-STATIC	N/A
ASTM C1028 - STATIC/FRICTION	N/A
ASTM D1335 - TUFT BIND	12 LB
ASTM F2765 - LEAD LEVELS	<0.01 PPM
ASTM D2859 - FLAMMABILITY (PILL TEST)	PASS
ASTM E648 - FLAMMABILITY (CRITICAL RADIANT FLUX)	CLASS I
ASTM 5034 - GRAB TEAR STRENGTH	N/A
ASTM F1951 - ADA WHEELCHAIR	N/A
ASTM F1551 - WATER PERMEABILITY	>600 IN/HR
ASTM E108 - FIRE TEST (ROOF DECKS)	N/A
ASTM E84 - SURFACE FLAMMABILITY/SMOKE DENSITY	N/A
ASTM 1292 - IMPACT ATTENUATION	PASS



PET MAXX