





## HEATMAXX SOFT <sup>™</sup> 47

## **KEY FEATURES**

- 100% New Proprietary Nylon yarn construction delivers superior preformance that is "Soft as Poly, Strong as Nylon".
- NO INFILL REQUIRED! Fiber and turf design keeps fibers upright even in heavy use areas.
- Class A Fire Rating- the only turf warranted against reflective burns from Low E Windows.
- Certifiied for all indoor applications and exterior rooftops.
- 100% ADA wheelchair compliant and meets safety standards!



## HEATMAXX SOFT ™

**RECOMMENDED APPLICATIONS** 



PRODUCT SPECIFICATIONS

YARN TYPE:	100% NYLON
YARN COLOR:	VERDE & LIME GREEN
THATCH COLOR:	VERDE GREEN TAN
FACE WEIGHT:	47 OZ/SY
PILE HEIGHT:	1-3/8″
BACKING:	26 OZ BLACK URETHANE
WARRANTY:	15 YEAR PRO RATED WARRANTY

FOOT TRAFFIC











## HEATMAXX SOFT <sup>™</sup> 47

AATCC 134 - ANTI-STATIC	PASS	
ASTM C1028 - STATIC/FRICTION	PASS	
ASTM D1335 - TUFT BIND	16.5 LB	
ASTM F2765 - LEAD LEVELS	<0.01 PPM	
ASTM D2859 - FLAMMABILITY (PILL TEST)	PASS	
ASTM E648 - FLAMMABILITY (CRITICAL RADIANT FLUX)	PASS	
ASTM 5034 - GRAB TEAR STRENGTH	PASS	
ASTM F1951 - ADA WHEELCHAIR	COMPLIANT	
ASTM F1551 - WATER PERMEABILITY	>600 IN/HR	
ASTM E108 - FIRE TEST (ROOF DECKS)	CLASS A	
ASTM E84 - SURFACE FLAMMABILITY/SMOKE DENSITY	CLASS C	
ASTM 1292 - IMPACT ATTENUATION	PASS	

